

MARINE GENERATORS

100 GTA/GTAC ELECTRONIC GOV.

Three-Phase

General data

Maximum power (2)	77.8 kWe (97.2 kVA)	**Voltage**	480/277 V
Prime Power (3)	70.8 kWe (88.5 kVA)	**Amperage**	117 A
Frequency	60 Hz	**Phases**	3

Dimensions and weights

Total length without canopy	1760 mm	**Total length with canopy**	2150 mm
Total width without canopy	865 mm	**Total width with canopy**	865 mm
Total height without canopy	968 mm	**Total height with canopy**	1048 mm
Dry weight without canopy	988 Kg	**Dry weight with canopy**	1100 Kg

Engine

Base engine manufacturer	Deutz	**Diameter**	108 mm (4.25 in)
Model	SDZ-109E	**Stroke**	130 mm (5.12 in)
Type	Diesel, 4 stroke	**Compression ratio**	19:1
Engine RPM	1800	**Injection system**	Mechanical and direct
Number of cylinders	4	**Intake system**	Turbocharged
Total displacement	4764 cc	**SAE Flywheel housing**	SAE 2
Oil	SAE 15W40	**Coolant capacity**	17.5 L (4.62 gal)
Oil capacity	11 L (2.91 gal)	**Flywheel**	SAE 11 1/2
Power (1)	85 kW (115.6 CV)	**Coolant flow rate**	162.1 l/min (42.82 gal/m)
Salt water flow rate	130.4 l/min (34.45 gal/m)	**Intake air flow rate**	6.6 m3/m
Exhaust type	Wet exhaust elbow	**V-Belt Protection**	Optional
Emission compliance	-		

(1) Rating conditions according to ISO 3046 (100 kPa barometric pressure, 30 % relative humidity and 25 °C (77 ° F))
(2) Maximum output power: maximum power supplied by the genset at full load
(3) Prime Power: rated power according to ISO 3046 and ISO 8528-1. 10 % overload capacity one hour in twelve hours.
1 kW = 1,36 CV 1 kW = 1,36 HP (metric) 1 kW = 1,36 CH

Fuel system details

Consumption 25%	5.8 l/h (1.53 gal)	**Fuel type**	Diesel
Consumption 50%	11.2 l/h (2.96 gal)	**Fuel standards**	Fueloil diesel ASTM
Consumption 75%	16.1 l/h (4.25 gal)	**Injection pump type**	Individual
Consumption 100%	20.9 l/h (5.52 gal)	**Governor type**	Electronical

Electrical system

Battery voltage	24 V	**Stop solenoid type**	ETS
Starter motor	4 kW	**Alternator**	35 A
Earth isolated	Included	**IP 65 box kit**	Optional
SCO 11 double panel	Optional	**Current transformers**	Optional

Installation details

Exhaust hose inner diameter	90 mm (3.54 in)	**Maximum fuel lift height**	0.6 m (1.97 ft)
Sea water hose inner diameter	42 mm (1.65 in)	**Maximum raw water lift height**	4 m (157.48 in)
Fuel feeding hose inner diameter	12 mm (0.47 in)	**Maximum sea water temperature**	32 ° (89.6 °F)
Fuel return hose inner diameter	12 mm (0.47 in)	**Maximum installation angle (6)**	10 °
Minimum battery capacity	24 V 90 Ah		

Alternator details

Brand	Meccalte	**Cos Phi**	0,8
Model	ECP34 1S 4 C	**Tropicalized**	Yes
Regulator type	DSR	**Excitation system**	Brushless
Number of poles	4	**Voltage regulation accuracy (5)**	0,01
Isolation type (4)	H	**Alternator type**	Synchronous
IP protection	23	**Standards**	EN60034-1, IEC 60034-1

Standard equipment

Insulated ground wire	SCO11 control panel
Silentblocks	6 m electrical wiring extension
Oil extraction pump	User manual
Electronic actuator	Packaging

Optional accessories

Siphon break kit mandatory if generator is below waterline	Water Filters
Service/Cruise Kits: fuel and oil filters, raw water pump, impeller, alternator belt,...	Sea water cock
Dry Exhaust system	Welcome Kit
Wet Exhaust System	Kit Power Take-off

(4) Other protections available
(5) With load from 0 to 100%, speed variation from -2% up to +5%, power factor 0,8 linear and balanced load.
(6) In all directions
For other requirements please contact the Sales Dept.
46224 - 7/26

SCO 11 Panel

General Description

- Graphic LCD with light, 128 x 64 pixels display
- Genset measures (see Display Information)
- Configuration protected by user and password
- Running hour indication
- Multilingual
- Event history log
- Genset protections (see Alarm Management)
- Preheating function
- D+ pre-excitation Terminal
- Built-in PLC function
- CAN bus information with SAE J1939 protocol
- Maintenance hours control
- Dimensions 195 x 135 x 47 mm
- Panel cut-out 172 x 112 mm
- Weight 450 g

Alarm Management

- Shutdown (SD)
- Low/High Speed
- Overload*
- Short Circuit*
- Overcurrent*
- High/Low Voltage
- High/Low Frequency
- Emergency Stop
- Warnings (WRN)
- High engine coolant temperature
- Low oil pressure
- High/Low Battery Voltage
- Maintenance warning
- Sensor failure detection (FLS)
- MCU Alarm

Power Supply

- Voltage supply 12/24 DC with fuse protection
- Consumption 80mA (12V) or 51 (24V)

Operating Conditions

- Operating temperature -20+70 °C
- Humidity 95 % without condensation
- Front Panel Protection IP65
- Standard Conformity
- EN 61000-6-2, EN 61000-6-4, EN 61010-1
- EN 60068-2-6 (2÷25 Hz / ±1,6 mm; 25÷100 Hz / 4.0 g)
- EN 60068-2-30:2005 25/55°C, RH 95%, 48hours
- EN 60529 (front panel IP65, back side IP20)

Display Information

- Measurement
- L1-L3 Voltage (V)
- Frequency (Hz)
- Oil Pressure (bar)
- Coolant Temperature (°C)
- Battery Voltage (V)
- RPM
- Power* (kW)
- Apparent Power* (kVA)
- Current* (A)
- PF*
- Historical Log
- Alarm History

Operating modes

- OFF Mode
- MAN Mode (manual start/stop engine)
- AUT Mode (auto start/stop engine)

Optional: Parallel Kit Electrical Cabinet

General Description

- Control and Power box for parallel operation
- COMAP Inteligen200 Panel (See Panel Features)
- Current Transformers (See Alternator Measurements)
- Power Isolating Switch
- Automatic Synchronism
- Marine Generator Set Protections (See Alarm Management)
- Power and Control Electrical Protection
- Communication Control Cable Extensions (See Extensions)
- Power inputs and outputs
- Automatic or manual control switch
- Audible and visual alarm
- Can BUS communication with the control unit and the parallel box
- Emergency Stop button
- IP 65 Protection

Alarm Management

- Shut-down (SD)
- High engine coolant temperature
- Low oil pressure
- Over speed
- Overload
- Short circuit
- Battery charge failure
- High/low voltage
- High/Low Frequency
- Emergency stop button
- Remote alarms
- Warnings (WRN)
- High engine coolant temperature
- Low oil pressure
- High/low battery voltage
- Maintenance warning

Alternator Measurements

- Current transformers
- Allows the following readings:
- Current (A), Active Power (kW), Apparent Power (kVA) and PF
- Earth isolated transformers

Extension

- Control wiring. Box-Group (6/12/24 m)
- Mitsubishi / Deutz
- 60974209 / 60994210P - 6 m
- 60974212 / 60994212P - 12 m
- 60974213 / 60994213P - 24 m
- Wiring for communication between boxes (3/6/12 m)
- 60994503 - 3 m
- 60994522 - 6 m
- 60994521 - 12 m
- Remote panel extension (12/24/36 m)
- 60972104 - 12 m
- 60972105 - 24 m
- 60972110 - 36 m

Inteligen200 Panel Features

- Group and load Synchronization
- Marine generator set measures
- L1-L3 Voltage (V), frequency (Hz), Oil pressure (bar)
- Coolant temperature (ºC), battery voltage (V), RPM
- Power* (kW), Apparent Power* (kVA), Current* (A), PF*
- Remote panel
- 2 x 10 A Binary outputs
- History log
- Running hour indicator
- Multilanguage
- Configuration protected by password
- Integrated PLC
- Communication and Extension Module Plug-in
- 4G/LTE communication standard
- GPS

Optional Equipment

- Inteligen200 Remote Double Panel
- It allows the same operation and functionality as main Inteligen200
- They are connected with an RS485 port
- Remote panel extension (12/24/36 m)
- Binary and Communication Input/Output Extension Module

Dimensions











Authorized dealer

Detailed drawings, brochures and manuals are available on the web soleadvance.com.
Technical specifications, data and presentation are subjected to variations, changes and updates without prior notice.
Non-contractual information.

CERTIFIED ISO 9001